

Vertical Heat Shrinkable Fiber Optic Splice Closure

Part Number	Number of inlet/outlet ports	Capacity(Cores)	Size
HFOCL-DH1	5	Bunchy: 6-48	φ178x299
HFOCL-DH2	5	Bunchy: 12-96, Ribbon: up to 288	φ190x435
HFOCL-DH3	8	Bunchy: 12-240, Ribbon: up to 576	φ220x455

Features

The box add aging-resistant in imported high tensile construction plastic out-faster is made up of stainless steel.
Overlap structure in splicing tray easy to install
Suitable for ordinary fiber and ribbon fiber
Perfect leak proofness and fine function
Perfect and reliable sealing operations
Fiber-bending radium guaranteed more than 40mm□
Full accessories for convenient operations
Fiber optic splice closure can be used repeatedly
High reliability
For aerial, and direct buried applications

Specifications:

Temperature: -40 to +80 degrees Celsius
Atmosphere: 70 to 106kpa
Sealing property at normal temperature: Internal pressure: 70 KPa, without decrease in 72 hours
High temperature sealing property: internal pressure: 70KPa, without decrease in 168 hours at 60 degree
nsulated resistance: >2×104MΩ
Intensity: 15KV (DC) not being broken down, has no flying arc
Add ional Loss: No additional loss when optic fibers are winded in the splice trays
The-aging time of the material of the enclosure is beyond 20 years

For detailed inquiry please contact our sales team at: sales@huihongfiber.com .